

HSS-Co 8%

- Per la foratura di metalli, legno, plastica e resine sintetiche

	art.	Ø mm	Ø "	A	g
004500016	450 16	16	(5/8)	57	21
004500017	450 17	17	(11/16)	57	32
004500019	450 19	19	(3/4)	51	30
004500020	450 20	20	-	51	29
004500021	450 21	21	(13/16)	51	37
004500022	450 22	22	(7/8)	51	43
004500024	450 24	24	(15/16)	51	49
004500025	450 25	25	(1")	51	58
004500027	450 27	27	(1"1/16)	51	65
004500029	450 29	29	(1"1/8)	51	73
004500030	450 30	30	(1"3/16)	51	81
004500032	450 32	32	(1"1/4)	51	70
004500033	450 33	33	(1"5/16)	51	90
004500035	450 35	35	(1"3/8)	51	99
004500037	450 37	37	(1"7/16)	51	107
004500038	450 38	38	(1"1/2)	44	72
004500040	450 40	40	(1"9/16)	44	77
004500041	450 41	41	(1"5/8)	44	83
004500043	450 43	43	(1"11/16)	44	89
004500044	450 44	44	(1"3/4)	44	95
004500046	450 46	46	(1"13/16)	44	102
004500048	450 48	48	(1"7/8)	44	97
004500051	450 51	51	(2")	44	120
004500052	450 52	52	(2"1/16)	44	128
004500054	450 54	54	(2"1/8)	44	123
004500057	450 57	57	(2"1/4)	44	148
004500059	450 59	59	(2"5/16)	44	148
004500060	450 60	60	(2"3/8)	44	165
004500064	450 64	64	(2"1/2)	44	180
004500065	450 65	65	(2"9/16)	44	185
004500067	450 67	67	(2"5/8)	44	193
004500068	450 68	68	-	44	200
004500070	450 70	70	(2"3/4)	44	211
004500073	450 73	73	(2"7/8)	44	227
004500076	450 76	76	(3")	44	249
004500079	450 79	79	(3"1/8)	44	264
004500083	450 83	83	(3"1/4)	44	261
004500086	450 86	86	(3"3/8)	44	279
004500089	450 89	89	(3"1/2)	44	327
004500092	450 92	92	(3"5/8)	44	311
004500095	450 95	95	(3"3/4)	44	337
004500098	450 98	98	(3"7/8)	44	388
004500102	450 102	102	(4")	44	413
004500105	450 105	105	(4"1/8)	44	398
004500108	450 108	108	(4"1/4)	44	426
004500111	450 111	111	(4"3/8)	44	446
004500114	450 114	114	(4"1/2)	44	466
004500121	450 121	121	(4"3/4)	44	527
004500127	450 127	127	(5")	44	617

